



ALL INTERNAL SURFACES ON THE TRENCH TRAY PAINTED BLACK.

OUTPUT WATTS / METER  
22mm DIA. ELEMENT - DOUBLE ROW  
FLOW RATE 0.303 LT / SEC.

REF	300mm DEEP	200mm DEEP	150mm DEEP
A	300	200	150
B	290	190	140
C	265	165	115
D	100	100	75
E	180	80	35

TRENCH DEPTH	Δ T 42°	Δ T 48°	Δ T 52°	Δ T 58°
300	520	750	845	985
200	555	680	765	895
150	520	625	705	830

OUTPUT WATTS / METER  
22mm DIA ELEMENT - SINGLE ROW  
FLOW RATE 0.303 LT / SEC.

REF	300mm DEEP	200mm DEEP	150mm DEEP
A	300	200	150
B	290	190	140
C	265	165	115
D	100	100	75
E	180	80	35

TRENCH DEPTH	Δ T 42°	Δ T 48°	Δ T 52°	Δ T 58°
300	342	418	470	545
200	300	375	425	495
150	280	345	390	455

TITLE  
SECTION SHOWING TYPICAL FLOOR TRENCH CASING -  
300mm & 200mm WIDE.



**B. G. PERIMETER SYSTEMS LTD.**  
ENTERPRISE HOUSE, PACKET BOAT LANE,  
COWLEY, UXBRIDGE, MIDDLESEX UB8 2JP.  
Telephone: (01895) 441794/5/6  
Fax No: (01895) 448597

SCALE  
N.T.S

DRAWN J.A  
CHK'D  
DATE 11/1/07

DRG. No.  
PM/4069

REV.	REVISION	DATE

